

JinHang 50W LED Floodlight V6 6000K Grey





MODEL	CS-JH-FL6-50W-GREY-6000K-CLEAR-NZ	**HOUSING COLOUR**	Grey
	CS-JH-FL6-50W-GREY-6000K-FROST-NZ	**MATERIAL**	Aluminium, Tempered Glass (Clear / Frost)
INPUT VOLTAGE (V)	100-300V AC	**IP**	IP66
PROTECTION CALSS	CLASS I	**IK**	IK06
POWER FACTOR (PF)	0.9	**OPERATING TEMPERATURE (°C)**	-40°C to +50°C
WATTAGE (W)	50W	**DIMMABLE (Y/N)**	NA
FLICKER FREE (Y/N)	NA	**DIMMING TYPE**	NA
LUMEN OUTPUT (LM)	4,000LM	**INSTALLATION TYPE**	Surface Mounting
EFFICACY (LM/W)	80LM/W	**DIMENSION (mm)**	180 x 200 x 38.6
COLOUR TEMPERATURE (K)	6000K	**NET WEIGHT**	1.35kg
BEAM ANGLE (°)	110°	**LIFETIME**	45,000 Hours
CRI (Ra)	80	**WARRANTY**	5 Years
SDCM	<7		

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order