

Jinhang V2 40W Linear LED Batten





MODEL	JH-LB02-40W-Black-4000K-NZ JH-LB02-40W-Black-6000K-NZ JH-LB02-40W-White-4000K-NZ JH-LB02-40W-White-6000K-NZ	**UGR**	≤19
INPUT VOLTAGE (V)	AC200-240V	**FINISH & MATERIAL**	Black / White Aluminum + PC
PROTECTION CALSS	Class I	**IP**	IP20
POWER FACTOR (PF)	PF>0.85	**AMBIENT TEMPERATURE (°C)**	Ta 45°C
WATTAGE (W)	40W	**OPERATING TEMPERATURE (°C)**	-20 to +45 °C
FLICKER FREE	Yes	**DIMMABLE**	No
LUMEN OUTPUT (LM)	4000 LM	**INSTALLATION TYPE**	Surface mount
EFFICACY (LM/W)	≥100 LM/W	**DIMENSION (mm)**	L1200 x W90 x H28 mm L1200 x W90 x H48 mm with surface mounting bracket
COLOUR TEMPERATURE	4000K / 6000K	**NET WEIGHT (kg)**	1.8kg with surface mounting bracket
BEAM ANGLE (°)	110°	**LIFESPAN (hr.)**	50,000 hr.
CRI (Ra)	>80	**WARRANTY (yr.)**	5 yr.
SDCM	<5		

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order