
LiteLighting G2 28W LED Panel - 5000K 600x300 IP44





MODEL	LL-PL02-3060-IP44-28W-5000K-NZ	**HOUSING COLOUR**	White
INPUT VOLTAGE (V)	220-240V AC	**MATERIAL**	Polycarbonates
PROTECTION CALSS	Class II	**IP**	IP44
POWER FACTOR (PF)	>0.9	**OPERATING TEMPERATURE (°C)**	-20°C to +45°C
WATTAGE (W)	28W	**DIMMABLE (Y/N)**	No
FLICKER FREE (Y/N)	Yes	**DIMMING TYPE**	NA
LUMEN OUTPUT (LM)	2,800 LM	**INSTALLATION TYPE**	Ceiling Mount
EFFICACY (LM/W)	100 LM/W	**DIMENSION (mm)**	L595 x W295 x H10 mm
COLOUR TEMPERATURE (K)	5000K	**NET WEIGHT (kg)**	1.3 Kg
BEAM ANGLE (°)	120°	**LIFESPAN (hr.) @L70B50**	50,000 hrs.
CRI (Ra)	>80	**WARRANTY (yr.)**	3 yrs.
UGR	<19		

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order