
GPPL 32W LED Panel Tri-colour 1195x295 IP20





MODEL	CS-GPPL-A1-S14-32-11-01-A-2-C-NZ	**HOUSING COLOUR**	White
INPUT VOLTAGE (V)	AC 220-240V; 50/60Hz	**MATERIAL**	Aluminium + Polycarbonate
PROTECTION CALSS	Class II	**IP**	IP20
POWER FACTOR (PF)	0.9	**IK**	N/A
WATTAGE (W)	32W	**OPERATING TEMPERATURE (°C)**	-10°C to +40°C
FLICKER FREE (Y/N)	Yes	**DIMMABLE (Y/N)**	No
LUMEN OUTPUT (LM)	3,600 LM	**DIMMING TYPE**	N/A
EFFICACY (LM/W)	95~110 LM/W	**INSTALLATION TYPE**	Suspension
COLOUR TEMPERATURE (K)	Tri-colour (3000K-4000K-6000K)	**DIMENSION (mm)**	1195 x 295 x 10 mm
BEAM ANGLE (°)	120°	**NET WEIGHT (kg)**	2.4 kg
CRI (Ra)	80	**LIFESPAN (hr.)**	25,000 hrs.
SDCM	<6	**WARRANTY (yr.)**	3 yrs.
UGR	22		

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order