
JinHang 24W Double LED Wall Light V2



SWL2
(with Sensor)



WL2
(without Sensor)



MODEL	JH-SWL2-V2-24W-MIC-3000K-NZ	**HOUSING COLOUR**	Black
	JH-SWL2-V2-24W-MIC-6000K-NZ	**MATERIAL**	Polycarbonate
	JH-WL2-V2-24W-3000K-NZ	**IP**	IP54
	JH-WL2-V2-24W-6000K-NZ	**OPERATING TEMPERATURE (°C)**	-20ºC to +40ºC
INPUT VOLTAGE (V)	200-240V AC	**DIMMABLE (Y/N)**	NA
POWER FACTOR (PF)	PF>0.9	**DIMMING TYPE**	NA
WATTAGE (W)	2X12W	**INSTALLATION TYPE**	Wall & Surface mount
LUMEN OUTPUT (LM)	3000K: 1,900LM 6000K: 2,200LM	**DIMENSION (mm)**	Base: W166mm x H126mm Lamp: W80mm x H100mm (without sensor part)
EFFICACY (LM/W)	3000K: 80LM/W 6000K: 90LM/W	**NET WEIGHT (kg)**	0.8Kg
COLOUR TEMPERATURE (K)	3000K, 6000K	**LIFETIME@L70B50**	40,000 Hours
BEAM ANGLE (°)	SWL2: Microwave 2-12M (Radius), 180º Detection Angle WL2: 180º	**WARRANTY**	3 Years
CRI (Ra)	>80		

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order