Emerex 4ft Wireguard Fitting





MODEL	CS-MRX-WG122-EMERGENCY-NZ	**HOUSING COLOUR & MATERIAL**	White, Powder Coat Folded Sheet Metal
LED BRAND	Osram	**IP**	20
DRIVER BRAND	SYNNOVATE	**IK**	09
INPUT VOLTAGE (V)	230V	**OPERATING TEMPERATURE (°C)**	0 – 40°C
POWER FACTOR (PF)	0.95	**MAINTAIN/NON-MAINTAIN OPERATION**	Switchable in between
WATTAGE (W)	36W	**DIMMABLE**	YES
FLICKER FREE	YES	**INSTALLATION TYPE**	Surface Mount – Wall / Ceiling
LUMEN OUTPUT (LM)	4,000LM	**DIMENSION (mm)**	1270 x 130 x 110
EFFICACY (LM/W)	111LM/W	**NET WEIGHT (kg)**	3.0
COLOUR TEMPERATURE	4000K	**LIFESPAN (Hours)**	50,000
BEAM ANGLE (°)	120°	**WARRANTY (Years)**	3
CRI (Ra)	84	**COMPLIANCE**	AS/NZS 2293, AS/NZS 60598, RCM

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order