
Emerex Premium Surface Mounted Spitfire





MODEL	CS-MRX-EMSMD63-NZ	**HOUSING COLOUR & MATERIAL**	White, ABS
LED BRAND	Osram	**IP**	65
DRIVER BRAND	SYNNOVATE	**IK**	07
INPUT VOLTAGE (V)	230V	**OPERATING TEMPERATURE (°C)**	0 – 40°C
POWER FACTOR (PF)	0.95	**MAINTAIN/NON-MAINTAIN OPERATION**	Non-maintained
WATTAGE (W)	5W	**EMERGENCY CLASSIFICATION**	D63
FLICKER FREE	YES	**DIMMABLE**	NA
LUMEN OUTPUT (LM)	>485LM	**INSTALLATION TYPE**	Surface Mount – Ceiling
EFFICACY (LM/W)	97LM/W	**DIMENSION (mm)**	130 x 130 x 35
COLOUR TEMPERATURE	6500K	**NET WEIGHT (kg)**	0.5
BEAM ANGLE (°)	170°	**LIFESPAN (Hours)**	50,000
CRI (Ra)	84	**WARRANTY (Years)**	3
COMPLIANCE		AS/NZS 2293, AS/NZS 60598, RCM	

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order