



SHOP SMART. SHOP VALUE
SHOP *differently*



MECCA Heatshrink Thin Wall Glued Tube PRE3.2/AFT1 Black 1.22M



Application: Adhesive heatshrink for a wide variety of cable termination, insulation & protection

Feature: Shrink ratio 3 : 1
Flame Retardant
UV & Corrosion Resistance
Excellent sealing against water & moisture

Operating Temperature: -45°C to 125°C

Compliance: UL & RoHs

Size & Pack Detail:

Part No.	Before Shrink OD	After Shrink OD	Length
CS-MECCA-HST-TWGL3-1-BK-NZ	3.2mm	1mm	1.22 Meters



Heatshrink Tube
Dual Wall with Glued
3 : 1 Ratio



Technical Specification:

Property	Test Method	Performance
Tensile Strength	ASTM D 2671	≥ 10.4MPa
Elongation at Break	ASTM D 2671	≥ 300%
Tensile Strength (Heat Aged)	UL224 158°C X 168hr	≥ 7.3MPa
Elongation at Break (Heat Aged)	UL224 158°C X 168hr	≥ 200%
Flammability	ASTM D2671B	Self Extinguish within 30s
Dielectric Strength	IEC243	≥ 15KV/mm
Volume Resistivity	ASTM D876	≥ 10 ¹⁴ Ω.cm
Hot Melt Adhesive Property		
Water Absorption	ASTM D570	< 0.5%
Sofening Point	ASTM E28	90 ± 5 °C
Strength of Pearing (PE)	ASTM D1000	80N/25mm
Strength of Pearing (AL)	ASTM D1000	120N/25mm



MOORABBIN

131-133 Keys Road
Moorabbin VIC 3189

ALTONA

1 Drake Boulevard
Altona VIC 3018

ALBION

35 Sandgate Road
Albion QLD 4010

AUCKLAND

10 Fairfax Avenue, Penrose
Auckland 1061, New Zealand

sales@jh.market

www.jh.market

sales@jhmarket.co.nz

jhmarket.co.nz

AU National: 1300 000 808

Queensland: 1300 000 707

NZ National: 0800 748 848