
Rafe 24W Surface Mount Downlight IP65 WH





MODEL	CS-CGD-LC1517R-01-3000K-WH-NZ CS-CGD-LC1517R-01-4000K-WH-NZ CS-CGD-LC1517R-01-5000K-WH-NZ	**UGR**	<19
LED BRAND & TYPE	Bridgelux COB	**HOUSING COLOUR**	WHITE
INPUT VOLTAGE (V)	220-240V, 50/60Hz	**MATERIAL**	ALUMINUM
PROTECTION CALSS	CLASS I	**IP**	IP65
IC-4 RATED (Y/N)	YES	**IK**	NA
POWER FACTOR (PF)	0.9	**OPERATING TEMPERATURE (°C)**	-20°C to +40°C
WATTAGE (W)	24W	**DIMMABLE (Y/N)**	Yes
FLICKER FREE (Y/N)	YES	**DIMMING TYPE**	Traic-dimming
LUMEN OUTPUT (LM)	2160LM	**INSTALLATION TYPE**	SURFACE MOUNTED
EFFICACY (LM/W)	90LM/W	**DIMENSION (mm)**	Ø100 x H140 mm
COLOUR TEMPERATURE (K)	3000K / 4000K / 5000K	**NET WEIGHT (kg)**	1.1kg
BEAM ANGLE (°)	60°	**LIFESPAN (hr.) @L70B50**	50,000 HR
CRI (Ra)	90	**WARRANTY (yr.)**	3 YEARS
SDCM	<3		

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order